

# BATTERY STACKER

## FEEL THE DIFFERENCE

- Small Turning Radius
- Easy to Operate
- Low Maintenance Cost



Drive Unit-Optional  
for fully auto type



SD1000-16

SD650-16



SDW1000-25



Battery Meter



Soft-up function Patent Right Application  
(for SD1500-15 & SDW1000-25 only)



Small Built-in Charger



SD1500-15

## SPECIFICATIONS

MODEL	SD1500-15	SDW1000-25	SD650-16	SD1000-16	SD1000-16L
CAPACITY	1500 kg	1000 kg	650 kg	1000 kg	1000 kg
MAX. HEIGHT	1500 mm	2500 mm	1600 mm	1600 mm	1600 mm
MIN. HEIGHT	95 mm	95 mm	(80) 95 mm	(80) 95 mm	(80) 95 mm
FORK LENGTH	850 mm	850 mm	650 mm	800 mm	1100 mm
FORK WIDTH	150 mm	125 mm	125 mm	125 mm	135 mm
ADJUSTABLE FORK WIDTH	325 mm - 750 mm	275 mm - 725 mm	265 mm - 650 mm	265 mm - 600 mm	285 mm - 900 mm
OVERALL HEIGHT	2050 mm	2100 mm	1950 mm	1950 mm	1950 mm
OVERALL WIDTH	810 mm	780 mm	700 mm	650 mm	950 mm
OVERALL LENGTH	1650 mm	1650 mm	1300 mm	1500 mm	1800 mm
LIFTING TIME	Approx. 30sec	Approx. 30 sec	Approx. 17 sec	Approx. 25 sec	Approx. 25 sec
BATTERY CHARGER	Built-In Type AC 240V single phase				
BATTERY	DC 12V				
NET WEIGHT	470 kg	510kg	210 kg	270 kg	300 kg

• All specifications are subject to change without prior notice.